

### OffPeak Technologies - HMI Product Overview

| Model Number | Screen Size Type   | Resolution & Aspect Ratio | CPU Type & Speed   | Flash RAM (NOR) MB | SDRAM MB | Nand Flash MB | Battery Backed Memory (user defined) | OS       | Ethernet | Serial  | USB Host | USB Slave | RTC | Memory Card Slot |
|--------------|--------------------|---------------------------|--------------------|--------------------|----------|---------------|--------------------------------------|----------|----------|---------|----------|-----------|-----|------------------|
| PT043        | 4.3" TFT LCD QVGA  | 480x272 16:9              | Risc 32 bit 200Mhz | 8                  | 32       | 128           | 128Kb ~ 1Mb                          | HMI RTOS | YES      | 3 ports | 1        | 1         | YES | Micro SD         |
| PT056        | 5.6" TFT LCD QVGA  | 320x234 4:3               | Risc 32 bit 200Mhz | 8                  | 32       | 0             | 128Kb ~ 1Mb                          | HMI RTOS | NO       | 3 ports | 1        | 1         | YES | Micro SD         |
| PT056-L      | 5.6" TFT LCD QVGA  | 320x234 4:3               | Risc 32 bit 200Mhz | 8                  | 32       | 0             | 128Kb ~ 1Mb                          | HMI RTOS | NO       | 3 ports | 1        | 1         | YES | Micro SD         |
| PT070        | 7.0" TFT LCD WVGA  | 800x480 16:9              | Risc 32 bit 200Mhz | 8                  | 64       | 128           | 128Kb ~ 1Mb                          | HMI RTOS | YES      | 3 ports | 1        | 1         | YES | Micro SD         |
| PT070-L      | 7.0" TFT LCD WVGA  | 800x480 16:9              | Risc 32 bit 200Mhz | 8                  | 64       | 128           | 128Kb ~ 1Mb                          | HMI RTOS | YES      | 3 ports | 1        | 1         | YES | Micro SD         |
| PT080        | 8.0" TFT LCD SVGA  | 800x600 4:3               | Risc 32 bit 200Mhz | 8                  | 64       | 128           | 128Kb ~ 1Mb                          | HMI RTOS | YES      | 3 ports | 1        | 1         | YES | Micro SD         |
| PT100        | 10.1" TFT LCD SVGA | 1024x600 16:9             | Risc 32 bit 200Mhz | 8                  | 64       | 128           | 128Kb ~ 1Mb                          | HMI RTOS | YES      | 3 ports | 1        | 1         | YES | Micro SD         |
| PT104        | 10.4" TFT LCD SVGA | 800x600 4:3               | Risc 32 bit 200Mhz | 8                  | 64       | 128           | 128Kb ~ 1Mb                          | HMI RTOS | YES      | 3 ports | 1        | 1         | YES | Micro SD         |
| PT150        | 15.0" TFT LCD SVGA | 1024x768 16:9             | Risc 32 bit 200Mhz | 8                  | 64       | 128           | 128Kb ~ 1Mb                          | HMI RTOS | YES      | 3 ports | 1        | 1         | YES | Micro SD         |